



**DIMENSIONS PNEUS NANKANG SEMI SLICK homologués route DOT et E**

NANKANG NS2 R				
diamètres roues	largeurs jantes	dimensions	charge	vitesse
13"	5-6,5	185/60	84	V
13"	5-6,5	175/50	72	V
13"	5-6,5	175/60	77	V
14"	5-6,5	185/60	86	V
15"	5-6,5	165/55	75	V
15"	5-6,5	165/50	73	V
15"	5,5-7,5	195/50	86	W
15"	5,5-7,5	195/55	89	W
15"	5,5-7,5	205/50	89	W
16"	5,5-7,5	195/50	86	W
16"	5,5-7,5	195/45	84	W
16"	5,5-7,5	205/55	89	W
16"	6,5-7,5	205/45	89	W
16"	6,5-8	225/45	91	W
17"	6,5-8	225/45	91	W
17"	7-8,5	215/45	91	W

**AR1**

Size	Load Index	Speed Index	Rim Width (Inch)	OD (mm)	SW (mm)
235/45ZR17	97(XL)	Y	7.5" - 9"	644	236
225/45ZR17	94(XL)	W	7" - 8.5"	634	225
215/45ZR17	91(XL)	W	7" - 8"	626	213
225/45ZR16	93(XL)	W	7" - 8.5"	608	225
205/45ZR16	87(XL)	W	6.5" - 7.5"	590	206
225/45ZR15	91(XL)	W	7" - 8.5"	583	225
235/45R13	91(XL)	V	7.5" - 9"	540	236
195/50ZR16	88(XL)	W	5.5" - 7"	602	201
205/50ZR15	89(XL)	W	5.5" - 7.5"	587	214
195/50R15	86(XL)	V	5.5" - 7"	577	201
175/50R13	72	V	5" - 6"	506	182
185/60R14	82	V	5" - 6.5"	578	189
205/60R13	90(XL)	V	5.5" - 7.5"	576	209
185/60R13	80	V	5" - 6.5"	552	189
165/60R12	71	H			